

## EXTINGUISHING AGENTS- ABC EXTING. POWDER TO THE STANDARD IRAM 3569:2009

		ABC 55
Main Components		Mono Ammonium Phosphate and Ammonium Sulphate
MAP Content	g/100g	55
Bulk Density (*)	g/ml	0.87-0.95
Sieve Analysis (*) Retained on 425 µm Retained on 150 µm Retained on 75 µm Retained on 45 µm	%	0 8-14 36-48 58-70
Moisture Content (*)	g/100g	<0.25
Water Repellency (*)	g/100g	3
Resistance to Caking and Lumping (*)		Positive
Resistance to Heath (*)	-	Positive
Waterproofing (*)	g/100g	>97
Resistance to Cold (*)	Sg	5
Electrical Insulation (*)	Kv	5
Powder Melting (*)	-	Positive
Extinction in Laboratory (*)	G	Positive to 1,5 g.

(\*)All the products are manufactured according to the Standard IRAM 3569:2009

Physical Risks: No toxicological hazards, neither during handling nor during the application of the extinguisher. (Ecotoxicity Test EC 50)

Durability: Products durability is guaranteed for at least 5 years, while no change or deformation in its properties occur and as long as manufacturer's instructions concerning handling and storage are followed.

QUÍMICA 21, S.L. reserves its right for any possible modification.